Elettro C.F. s.r.l.
via Miglioli, 24 40024 - Castel San Pietro Terme (Bologna) Italy
Telefono +39 051941453 - +39 0516942026 - FAX +39 051944602
C.F. e Registro Imprese BO n. 00706680378 - P.I. 00521381202 - Capitale Sociale 72.320,00 i.v.

Les détails du produit:

Code: S00293 **Modèle:**SYNERGIC MIG 315



Three-phase compact MIG MAG welding machine, on wheels, supplied with 15 welding torch and earth cable.

-It is suitable to weld steel, stainless steel, aluminium and galvanised metal plate.
-Synergetic-type generator with microprocessor for automatic welding current and wire speed adjustment via 21 pre-stored programs.
-It is possible to handle welding parameters such as spot welding, soft start, burn-back, post gas, and 2 stroke – 4 stroke (manual – automatic) welding.
-Multiple impedance outlet for improved welding characteristic adjustment.
-Possibility to connect a push-pull torch for 0.6 to 1.0 diameter aluminium welding.
-Possibility to update the software with new synergy curves if any.
-Highly stable thanks to large-diameter rear wheels.

Fiche technique:

Code	S00293
Item	SYNERGIC MIG 315
Input Voltage	3x230/400V 50-60Hz
Absorbed power	40% 6,9 KVA
MIN-MAX Welding current	15 – 250 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	40% 200A - 60% 160A - 100% 125A
Regulation steps	N° 2 x 6
Wire size (solid)	Ø 0,6 - 0,8 - 0,9 - 1,0 Al-Fe / 0,8 - 0,9 - 1,0 Inox / 0,8 - 0,9 - 1,0 Cu-Si 3% mm
Max. wire spool size	Ø 300 mm / 15 kg.
Protection class	IP21C
Construction standards	EN 60974 – 1 / EN 60974 - 10
Dimensions	506x897x872h mm
Weight	78 kg

Elettro C.F. s.r.l.
via Miglioli, 24 40024 - Castel San Pietro Terme (Bologna) Italy
Telefono +39 051941453 - +39 0516942026 - FAX +39 051944602
C.F. e Registro Imprese BO n. 00706680378 - P.I. 00521381202 - Capitale Sociale 72.320,00 i.v.

Accessoires:



384024 *(optional)* Adapter for wire reels of 15 kg. D. 300



309263 *(optional)* Welding helmet with auto-dimming LDC filter BEST VISION,



535011 3 m, M 15 torch



535012 *(optional)* Torche m 15, 4 m



535028 *(optional)* 4m,PUSH-PULL P3KP torch