

## Detalle del producto:

**Código:** C00405**Modelo:** BOOSTER 2200/4400

### PORTABLE BOOST STARTER AND RECHARGEABLE POWER SUPPLY SOURCE

It is ideal for any application where a portable powerful quick-start or/and a long lasting power source is needed.

Designed for operating mostly at 12V and occasionally at 24V, it can be used as:

- A battery charger (12V/24V).
- An emergency starter.
- An additional power source for vehicles (memory saver).
- A multipurpose additional power source (for electrical 12V or 24V devices).

It is rechargeable by plugging the power supply LESA 8A into any 230V household outlet or by plugging the charging cable LESA1 into the cigarette lighter of the vehicle.

It can be stored in any position without the risk of acid leakage.

It comes with an automatic reset breaker, with protection circuits against peak tensions to protect the vehicle electronic system and with charge test button with LEDS.

It is equipped with an innovative and practical double connection for allowing the use at 12V with a starting current of 4400 amps and at 24V with a starting current of 2200 amps. It delivers a minimum of 650 constant amps.

Including, as standard: power supply LESA 8A, cigarette lighter charger cable LESA1, heavy-duty clamps with 6-wire copper cable.



**Ficha de datos:**

|                                     |                    |
|-------------------------------------|--------------------|
| Code                                | C00405             |
| Item                                | BOOSTER 2200/4400  |
| Supply voltage (single phase)       | 230 V              |
| Voltage                             | 12 V 24 V          |
| Peak current output                 | 4400 / 2200 A p    |
| Constant current output             | 650 A              |
| Charge voltage                      | max 14,9 V         |
| Recharge voltage                    | LESA 8A (12V 4 Ah) |
| Automatic power supply              | YES                |
| Charging cable 12V                  | LESA 1             |
| Insulated clamps                    | YES                |
| Sealed and maintenance free battery | 12/24V 22Ah        |
| Overload protection                 | YES                |
| Number of batteries                 | 2                  |
| Weight                              | 20 kg              |
| Dimensions                          | 370x125x300h mm    |
| Cable length                        | 1550 mm            |
| Cables section                      | 40 mm              |

**Accesorios:**