

## Detalle del producto:

**Código:** S00312

**Modelo:**INVERTER PRO MIG 465 PULSED

Three-phase inverter power source for MIG-MAG wire welding with PULSE synergic operation and "multi-process", i.e. able to weld also in TIG and MMA mode.

Supplied complete with power source, 4-roller wire feed unit ready for cooling, 5l horizontal cooling unit and power source cart.

It is suitable to weld steel, stainless steel and aluminium.  
It is suitable for welding with cored wire.

### MAIN FEATURES

- Minimised thermal alteration in the welding seam area even when thin parts are welded.
- Exceptionally good arc stability at low amp rating.
- Complete control and management of the variables determining the welding conditions with pulsed current, through the control panel.
- Synergic operation, that permits controlling the welding conditions through just one variable, all the others being preset and dependent on this.
- Wide range of memory stored synergic curves representing the most common welding operation conditions; new synergic curves can be afterwards added to the power source memory.
- With HD (high deposit) program allows to speed of a 30% at least the working time with pulse welding.
- The torch cooling unit can be controlled from the control panel.
- On request, an optional kit for Push-Pull torch is available (art. 540060) which permits using the most common brands of Push-Pull torches.
- On request, it's available a version with DOUBLE-PULSE operation.



**Ficha de datos:**

Code	S00312		
Item	INVERTER PRO MIG 465 PULSED		
Mode	MIG	TIG	MMA
Input Voltage	3x400V 50-60Hz	3x400V 50-60Hz	3x400V 50-60Hz
Absorbed power	40% 15,9 kVA - 60% 13,2 kVA - 100% 11,7 kVA	40% 15,9 kVA - 60% 13,2 kVA - 100% 11,7 kVA	40% 15,9 kVA - 60% 13,2 kVA - 100% 11,7 kVA
MIN-MAX Welding current	5-380A	5-380A	10-340A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	40% 380A - 60% 340A - 100% 310A	40% 380A - 60% 340A - 100% 310A	40% 340A - 60% 320A - 100% 280A
Stepless regulation	ELECTRONIC		
Wire size (solid)	0,9/1,0/1,2/1,6 Al - 0,8/0,9/1,0/1,2/1,6 Fe-Inox - 0,8/0,9/1,0/1,2 CuSi 3% - 1,2/2,4 Cored Ø mm	-	-
Max. wire spool size	Ø 300 mm 15 kg	-	-
Electrodes	-	-	Ø 2 - 6 mm
Protection class	IP 23		
Dimensions	780x1150x1450h mm		
Weight	125 kg		

**Accesorios:**


560101 CU55H - Horizontal 5 l cooling unit for torch



530347 (optional) Cable para soldadura TIG



540060 (optional) Interface kit for push-pull torches



540012 (optional) Aluminium welding kit for Ø 1-1,2 wire and for 3,5 m torch

---



540013 (optional) Aluminium welding kit for Ø 1,2-1,6 wire and for 3,5 m torch

---

356065 (optional) Wire guide liner kit for D. 1,0-1,2 Fe/stainless steel/cored wire for torch MIG 500A

---

356066 (optional) Wire guide liner kit for D. 1,2-1,6 Fe/stainless steel/cored wire for torch MIG 500A

---



535718 (optional) 4 m, ABITIG 26 torch with EURO type connection

---



535030 (optional) 3,5 m, MIG 500A torch, ready for cooling unit

---



535031 (optional) 3,5 m, MIG 500A torch, double up-down torch, ready for cooling unit

---



550041 WF4 STP - synergic 4-roll wire feeder ready for torch cooling unit

---



580003 Transport cart

---



530361 (optional) 10 m, extension for wire feed unit with copper cable diam. 70 mm<sup>2</sup> ready for cooling unit.

---



357502 (optional) Flowmeter with 2 gas pressure gauges

---



384024 (optional) Adapter for wire reels of 15 kg. D. 300

---



530360 (optional) 5 m, extension for wire feed unit with copper cable diam. 70 mm2 ready for cooling unit.

---



309263 (optional) Welding helmet with auto-dimming LDC filter BEST VISION,

---



535019 (optional) Antorcha MB 501D, 3 m, predisposta para la refrigeración con líquido

---



535020 (optional) Antorcha MB 501D, 4 m, predisposta para la refrigeración con líquido

---