

Product Detail:

Code: S00277

Model: PRO MIG 335

Three-phase power source for MIG-MAG wire welding.

To be used with 2-roller WF21 or 4-roller WF41 wire feed units. These wire feed units are equipped with 1,5 m long power source – wire feeder cart connection extension.

It is possible to add power source – wire feeder cart connection extensions of 4 or 9 m long.

It is suitable to weld steel, stainless steel and aluminium.

- "EURO" type connection for the torch.

- Signal of intervention of the thermostat.

- High number of adjustments to facilitate achievement of the best welding parameters.

- Electronic regulator for spot welding.

- Highly stable thanks to large-diameter rear wheels.



Technical Data:

Code	S00277.37
Item	PRO MIG 335
Input Voltage	3x230/400V 50-60Hz
Absorbed power	40% 11,2KVA
MIN-MAX Welding current	25 – 300 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	40% 250A - 60% 200A - 100% 160A
Regulation steps	N° 2x6
Wire size (solid)	Ø 0,6 - 0,8 – 1 - (1,2) mm SOLID
Max. wire spool size	Ø 300 mm / 15 kg.
Protection class	IP21C
Construction standards	EN60974 – 1 / EN60974-10
Dimensions	506x897x1245h mm
Weight	115 kg

Accessories:

540011 (optional) Aluminium welding kit for Ø 0,8 - 1 wire and 3m torch.



550034 (optional) WF 21 - 2-roll wire feeder with 1,5 m extension



530325 (optional) 4 m extension for wire feed unit with copper cable diam. 35mm2



530326 (optional) 9 m, extension for wire feed unit with copper cable diam. 35mm2



550035 (optional) WF 41 - 4-roll wire feeder with 1,5 m extension



540014 (optional) Aluminium welding kit for Ø 1,2 - 1,6 wire and 3m torch.



384024 (optional) Adapter for wire reels of 15 kg. D. 300



309263 (optional) Welding helmet with auto-dimming LDC filter BEST VISION,



535013 (optional) 3 m, M 25 torch



535014 (optional) 4 m, M 25 torch