

## Produktdetail:

**Code:** S00278

**Vorlage:**PRO MIG 395

Three-phase power source for MIG-MAG wire welding.

To be used with 2-roller WF21 or 4-roller WF41 wire feed units. These wire feed units are equipped with 1,5 m long power source – wire feeder cart connection extension.

It is possible to add power source – wire feeder cart connection extensions of 4 or 9 m long.

It is suitable to weld steel, stainless steel and aluminium.

- "EURO" type connection for the torch.

- Copper transformer.

- Signal of intervention of the thermostat.

- High number of adjustments to facilitate achievement of the best welding parameters.

- Electronic regulator for spot welding.

- Highly stable thanks to large-diameter rear wheels.



## Datenblatt:

Code	S00278.37
Item	PRO MIG 395
Input Voltage	3x230/400V 50-60Hz
Absorbed power	40% 16,0 KVA
MIN-MAX Welding current	35 – 380 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	40% 330A - 60% 270A - 100% 210A
Regulation steps	N° 2x8
Wire size (solid)	Ø 0,6 - 0,8 – 1 - 1,2 mm SOLID
Max. wire spool size	Ø 300 mm / 15 kg.
Protection class	IP21C
Construction standards	EN 60974 – 1 / EN 60974 – 10
Dimensions	506x897x1245h mm
Weight	122 kg

**Zubehör:**

540011 (optional) Aluminiumset für Drähte Ø 0,8 - 1 und für 3m Brenner.



550034 (optional) WF 21 - 2-roll wire feeder with 1,5 m extension



530325 (optional) 4 m extension for wire feed unit with copper cable diam. 35mm<sup>2</sup>



530326 (optional) 9 m, extension for wire feed unit with copper cable diam. 35mm<sup>2</sup>



550035 (optional) WF 41 - 4-roll wire feeder with 1,5 m extension



540014 (optional) Aluminiumset für Drähte Ø 1,2 - 1,6 und für 3m Brenner.



384024 (optional) Adapter for wire reels of 15 kg. D. 300



309263 (optional) Welding helmet with auto-dimming LDC filter BEST VISION,



535015 (optional) 3 m, M 36 Brenner



535016 (optional) 4 m, M 36 Brenner