Elettro C.F. s.r.l.
via Miglioli, 24 40024 - Castel San Pietro Terme (Bologna) Italy
Telefono +39 051941453 - +39 0516942026 - FAX +39 051944602
C.F. e Registro Imprese BO n. 00706680378 - P.I. 00521381202 - Capitale Sociale 72.320,00 i.v.

Les détails du produit:

Code: S00139 **Modèle:**MMA 2055



Single-phase inverter power source for MMA and TIG welding with contact start.

•Can weld with rutile and basic coated up to 5 mm diameter.
•Equipped with strong shoulder strap to carry the power source on user's shoulder.
•Can be fed by generators provided that they are equipped with electronic regulation of the tension, their power is at least 8 kVA and tension does not exceed 260V RMS.
•Features: adjustable Arc Force and Hot Start functions and Anti-Stick function.
•Predisposition for remote control for the adjustment of the current.
•Microprocessor control of the welding functions.
•High efficiency and low absorption from mains.
•TIG welding with start by contact.
•Negligible tungsten inclusion in TIG welding.
•Possibility of using 50 metre supply cables with no significant power losses.

Elettro C.F. s.r.l.
via Miglioli, 24 40024 - Castel San Pietro Terme (Bologna) Italy
Telefono +39 051941453 - +39 0516942026 - FAX +39 051944602
C.F. e Registro Imprese BO n. 00706680378 - P.I. 00521381202 - Capitale Sociale 72.320,00 i.v.

Fiche technique:

Code	S00139
Item	MMA 2055
Input Voltage	1x230V 50-60Hz
Installation power	5 kW
MIN-MAX Welding current	5 ÷ 200 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	35% 200A - 60% 150A - 100% 130A
Electrodes	Ø 1,6 ÷ 5 mm
Stepless regulation	ELECTRONIC
Protection class	IP23
Insulation class	H
Construction standards	EN60974-1 / EN60974-10
Dimensions	135x390x280h mm
Weight	9,5 kg

Elettro C.F. s.r.l.
via Miglioli, 24 40024 - Castel San Pietro Terme (Bologna) Italy
Telefono +39 051941453 - +39 0516942026 - FAX +39 051944602
C.F. e Registro Imprese BO n. 00706680378 - P.I. 00521381202 - Capitale Sociale 72.320,00 i.v.

Accessoires:

	S01705A.11	*(optional)*	Accessories kit for electrode welding with 3+2 m cables of 25 mm2, Texas 50
	535709	*(optional)*	4 m, SR 17 V torch, texas D. 50
	530137	*(optional)*	Earth cable for welding
	530330	*(optional)*	5 m long cable for remote control
	570006	*(optional)*	Remote control