Elettro C.F. s.r.l.
via Miglioli, 24 40024 - Castel San Pietro Terme (Bologna) Italy
Telefono +39 051941453 - +39 0516942026 - FAX +39 051944602
C.F. e Registro Imprese BO n. 00706680378 - P.I. 00521381202 - Capitale Sociale 72.320,00 i.v.

Les détails du produit:

Code: S00129 **Modèle:**MMA 2560 CELL



Three-phase inverter power source for MMA and TIG welding with lift start.

•It can weld with rutile, basic coated, aluminium and cellulosic electrodes up to 5 mm diameter.
•It can be fed by motor-driven generators equipped with electronic regulation of the tension, with a power at least of 8,5 kVA and not delivering a voltage greater than 440V RMS.
•Features: adjustable Arc Force and Hot Start functions and Anti-Stick function.
•Predisposition for remote control for the adjustment of the current.
•Microprocessor control of the welding functions.
•High efficiency and low absorption from mains.
•The welding mode MMA or TIG can be selected using the "welding start" functions and "lift" contact start on the torch.
•Negligible tungsten inclusion in TIG welding.
•Provided with a display that shows the amps, voltage and function menu.

Elettro C.F. s.r.l.
via Miglioli, 24 40024 - Castel San Pietro Terme (Bologna) Italy
Telefono +39 051941453 - +39 0516942026 - FAX +39 051944602
C.F. e Registro Imprese BO n. 00706680378 - P.I. 00521381202 - Capitale Sociale 72.320,00 i.v.

Fiche technique:

Code	S00129
Item	MMA 2560 CELL
Input Voltage	3x400V 50-60Hz
Installation power	6,5 kW
MIN-MAX Welding current	10 ÷ 250 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	40% 250A - 60% 220A - 100% 160A
Electrodes	Ø 1,6 ÷ 5 mm
Stepless regulation	ELECTRONIC
Protection class	IP23
Insulation class	H
Construction standards	EN60974-1 / EN60974-10
Dimensions	220x440x460h mm
Weight	18 kg

Elettro C.F. s.r.l.
via Miglioli, 24 40024 - Castel San Pietro Terme (Bologna) Italy
Telefono +39 051941453 - +39 0516942026 - FAX +39 051944602
C.F. e Registro Imprese BO n. 00706680378 - P.I. 00521381202 - Capitale Sociale 72.320,00 i.v.

Accessoires:



535717 *(optional)* 4m, ABITIG 26V TIG torch



S01704A.10 *(optional)* Accessories kit for electrode welding with 5+3,5 m cables of 35 mm2 and "texas" connection 50



309269 *(optional)* Helmet with auto-dimming LCD filter (9-13 DIN) MAXIVISION COLOR to protect face and eyes during welding.



357502 *(optional)* Flowmeter with 2 gas pressure gauges



580002 *(optional)* Transport cart



530138 *(optional)* Câble de terre pour le soudage



530330 *(optional)* 5 m long cable for remote control



570008 *(optional)* TIG foot control



570006 *(optional)* Remote control