

Les détails du produit:

Code: S00229

Modèle: MULTIWELD 185 SYNERGIC

The single-phase multipurpose inverter power source, model MULTIWELD 185 SYNERGIC, is suitable for welding alternately in MIG/MAG, MMA (stick electrode) and DC TIG ("lift" start) mode. It has a compact design, low weight and low absorption from mains. Thanks to all these characteristics, it's an ideal machine for maintenance, repair, installation and on site welding, but also for workshop works requiring versatility of use.

- Equipped with 2 displays that show the amps and voltage and the welding process selected.
- Equipped with EURO type connection for MIG/MAG and TIG torches.
- TIG welding with start by "lift" contact.
- Suitable to weld in MMA-SMAW mode both rutile and basic electrodes.
- Possibility to activate a security PASSWORD.
- Supplied with MIG torch and earth cable.

In the MIG/MAG mode:

- it is possible to select a synergic program according to the wire type and diameter as well as the shielding gas to be used;
- it has curves optimized for steel, stainless steel, aluminium, MIG brazing and flux cored wire. It's possible to store new programs;
- synergic programs for steel allow working with either mixed gasses or 100% CO₂;
- selecting the manual working mode, it is possible to modify the welding parameters;
- a dedicated control is provided for fine tuning the arc length.



Fiche technique:

Code	S00229		
Item	MULTIWELD 185 SYNERGIC		
Mode	MIG	TIG	MMA
Input Voltage	1x230V 50-60Hz		
Absorbed power	7,1 KVA 35%	5,4 KVA 35%	6,2 KVA 45%
MIN-MAX Welding current	15-170A	5-170A	10-130A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	35% 170A - 60% 120A - 100% 100A	35% 170 A - 60% 120 A - 100% 100A	45% 130A - 60% 115A - 100% 100A
Stepless regulation	ELECTRONIC		
Wire size (solid)	0,6-0,8-1,0 FE / 1,0 AL / 0,8 INOX / 0,8 CuSi3% / 0,9 Cored Ø mm	-	-
Max. wire spool size	Ø 200 mm / 5 kg.	-	-
Electrodes	Ø 1,6-3,25 mm		
Protection class	IP 23		
Construction standards	EN 60974 – 1 / EN 60974 - 10		
Dimensions	220x400x460h mm		
Weight	11,5 kg		

Accessoires:


530149 Earth cable


 S01703A.1 (optional) Accessories kit for electrode welding with 3+2 m cables of 16 mm², Texas 25


535011 Torche M15, 3 m



580002 (optional) Transport cart



535012 (optional) Torche m 15, 4 m



535718 (optional) 4 m, ABITIG 26 torch with EURO type connection

540004 (optional) Aluminium welding kit, with roll, for \varnothing 0,8 - 1 wire and 3m torch.

540003 (optional) Flowmeter for non-refillable cylinders



308649 (optional) Non-refillable cylinders holder



311000 (optional) Non-refillable argon+CO2 cylinder for steel and stainless steel.



311001 (optional) Non-refillable argon cylinder for aluminium
