Elettro C.F. s.r.l.
via Miglioli, 24 40024 - Castel San Pietro Terme (Bologna) Italy
Telefono +39 051941453 - +39 0516942026 - FAX +39 051944602
C.F. e Registro Imprese BO n. 00706680378 - P.I. 00521381202 - Capitale Sociale 72.320,00 i.v.

Les détails du produit:

Code: S00164 **Modèle:**TIG 1710 AC/DC HF



Single phase AC/DC INVERTER portable power source for TIG welding with high frequency and MMA-SMAW welding.
Equipped with high frequency start and pulsed arc mode. Suitable for welding of aluminium, brass and magnesium in TIG AC mode as well as iron, steel, stainless steel, copper in TIG DC mode. Its many functions make it suitable for a wide range of applications.

MAIN FEATURES
•Great arc stability.
•Top quality welding (in TIG AC mode) on aluminium and its alloys.
•In TIG AC, penetration and cleansing of welding bath are adjustable.
•In AC mode, frequency can be adjusted.
•Pulsed arc function to reduce thermal alteration and simplify welding of thin coil.
•In TIG mode, the arc may be started ether in high frequency (HF Start) or by contact (Contact Start).
•2-stage, 4-stage and 4 stage dual level functions.
•Possibility of storing up to 9 welding programs in memory which may be easily re-called.
•Presetting for remote control.
•In MMA-SMAW mode, it allows welding with rutile and basic coated electrodes.
•Possibility to be connected to motor-driven generators with an electronic regulator of the tension (not greater than 260V RMS) and a power equal to or greater than 4,5 kVA.
•Microprocessor control of welding functions.
•IP23 protection to allow open-air works.
• Manufactured in compliance with the IEC/EN 61000-3-12 standard by means of the PFC devices.
•Possibility to activate a security password.
•Small dimensions and light weight.
•Optional trolley for transport.

Elettro C.F. s.r.l.
via Miglioli, 24 40024 - Castel San Pietro Terme (Bologna) Italy
Telefono +39 051941453 - +39 0516942026 - FAX +39 051944602
C.F. e Registro Imprese BO n. 00706680378 - P.I. 00521381202 - Capitale Sociale 72.320,00 i.v.

Fiche technique:

Code	S00164	
Item	TIG 1710 AC/DC	
Mode	TIG	MMA
Input Voltage	1x230V 50-60Hz	
Installation power	3 kW	
MIN-MAX Welding current	5 ÷ 170 A	10 ÷ 140 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	35% 170A - 60% 145A - 100% 130A	35% 140A - 60% 125A - 100% 115A
Electrodes		Ø mm 1,6 ÷ 3,2
Stepless regulation	ELECTRONIC	
Protection class	IP 23	
Insulation class	H	
Construction standards	EN 60974-1 EN60974-10	
Dimensions	220x440x460h mm	
Weight	19 kg	

Elettro C.F. s.r.l.
via Miglioli, 24 40024 - Castel San Pietro Terme (Bologna) Italy
Telefono +39 051941453 - +39 0516942026 - FAX +39 051944602
C.F. e Registro Imprese BO n. 00706680378 - P.I. 00521381202 - Capitale Sociale 72.320,00 i.v.

Accessoires:

	S01705A.11	*(optional)*	Accessories kit for electrode welding with 3+2 m cables of 25 mm2, Texas 50
	580002	*(optional)*	Transport cart
	363307	*(optional)*	Foot control and TIG torch connector
	530137	*(optional)*	Earth cable for welding
	535805	*(optional)*	4 m, ABITIG 26 UP-DOWN torch
	535802	*(optional)*	4 m, ABITIG 26 torch
	570008	*(optional)*	TIG foot control
	570006	*(optional)*	Remote control
	530330	*(optional)*	5 m long cable for remote control