

Produktdetail:

Code: S00159

Vorlage:TIG 2081 DC HF

Single-phase inverter power source for TIG welding with high frequency and MMA-SMAW, TIG 2081 DC HF, is equipped with high frequency start, pulsed arc mode and is suitable for welding of iron, steel, stainless steel, copper and titanium. It welds coated rutile and basic electrodes. It's suitable for light-medium metal fabrication as well as for servicing in general.

MAIN FEATURES

- Great arc stability.
- Pulsed arc function to reduce thermal alteration and simplify welding of thin coil.
- 2-stage, 4-stage and 4 stage dual level functions.
- Possibility of welding with two preset welding current levels (dual level).
- Possibility of storing up to 9 welding programs in memory which may be easily re-called.
- Slope-down and post-gas adjustment.
- Presetting for remote control.
- In TIG mode, the arc may be started either in high frequency (HF Start) or by contact (Contact Start).
- In MMA-SMAW mode, it allows welding with rutile and basic coated electrodes.
- Forced air cooling through cooling tunnel.
- Microprocessor control of welding functions.
- Possibility to be connected to motor-driven generators with an electronic regulator of the tension (not greater than 260V RMS) and a power equal to or greater than 5 kVA.
- IP23 protection to allow open-air works.
- Manufactured in compliance with the IEC/EN 61000-3-12 standard by means of the PFC devices.
- Possibility to activate a security password.
- Small dimensions and light weight.
- Optional trolley for transport.



Datenblatt:

Code	S00159	
Item	TIG 2081 DC HF	
Mode	TIG	MMA
Input Voltage	1x230V 50-60Hz	
Installation power	4 kW	
MIN-MAX Welding current	5 ÷ 200 A	10 ÷ 160 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	35% 200A - 60% 170A - 100% 150A	35% 160A - 60% 130A - 100% 115A
Electrodes	Ø mm 1,6 ÷ 4	
Stepless regulation	ELECTRONIC	
Protection class	IP 23	
Construction standards	EN60974-1 / EN60974-10	
Dimensions	180x400x410h mm	
Weight	13 kg	

Zubehör:


535805 (optional) 4 m, ABITIG 26 UP-DOWN torch



535802 (optional) 4 m, ABITIG 26 torch



580002 (optional) Fahrwagen für Transport



530137 (optional) Earth cable for welding



S01705A.1
1 *(optional)* Zubehörset für das Elektrodenschweissen mit 3+2 m Kabel 25 mm², Texas 50



570006 *(optional)* Remote control



530330 *(optional)* 5 m long cable for remote control



570008 *(optional)* TIG foot control



363307 *(optional)* Foot control and TIG torch connector



309269 *(optional)* Helmet with auto-dimming LCD filter (9-13 DIN) MAXIVISION COLOR to protect face and eyes during welding.



540102 *(optional)* INOX FAST CLEAN KIT



357502 *(optional)* Druckminderer mit 2 Manometern