

## Produktdetail:

**Code:** S00258

**Vorlage:**MIG 2800

Three-phase compact MIG MAG welding machine, on wheels, supplied with M 15 welding torch and earth cable.

- It's available also a model with a 4 roller wire feeder.
- It's suitable to weld steel, stainless steel and aluminium.
- Possibility to adjust the welding parameters through 7 adjustment steps.
- Aluminium wire feeder that enables the adjustment of the pressure applied to the wire for having constant feeding and for decreasing wear of the feeding device.
- Possibility to adjust the spot welding time.
- Highly stable thanks to large-diameter rear wheels.



## Datenblatt:

Code	S00258
Item	MIG 2800
Input Voltage	3x230/400V 50-60Hz
Absorbed power	35% 7,8 kVA - 60% 5,5 kVA - 100% 4,5 kVA
MIN-MAX Welding current	15 – 250 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	35% 200A - 60% 140A - 100% 115A
Regulation steps	N° 1 x 7
Wire size (solid)	Ø 0,6 -0,8 - 1,0 mm SOLID
Max. wire spool size	Ø 300 mm / 15 kg.
Protection class	IP21
Construction standards	EN 60974 – 1 / EN60974-10
Dimensions	506x897x872h mm
Weight	62 kg

**Zubehör:**



540011 (optional) Aluminiumset für Drähte  $\varnothing$  0,8 - 1 und für 3m Brenner.



357502 (optional) Druckminderer mit 2 Manometern



384024 (optional) Adapter for wire reels of 15 kg. D. 300



540037 (optional) Holding kit for torches



309263 (optional) Welding helmet with auto-dimming LDC filter BEST VISION,



535011 3 m, M 15 Brenner



535012 (optional) M 15 Brenner, 4 m