

## Detalle del producto:

**Código:** S00287

**Modelo:** SYNERGIC PRO MIG 485

Three-phase power source for MIG-MAG welding.

It can be used with traditional 2 or 4 roller wire feed units, item WF20 or WF40, and with synergic 4 roller, wire feed units, item WF44.

Possibility to connect extensions for the connection of power sources to wire feed units of 5 or 10 metres.

Power source ready for water cooling.

It is suitable to weld steel, stainless steel and aluminium.

Equipped with:

-Signal of intervention of the thermostat.

-High number of adjustments to facilitate achievement of the best parameters.

-Multiple impedance outlet for improved welding characteristic adjustment.

-By using synergic wire feed units, it is possible to handle welding parameters such as spot welding, soft start, burn-back, post gas, and 2 stage – 4 stage welding modes.

-Highly stable thanks to large-diameter rear wheels.



## Ficha de datos:

|   |  |
|---|--|
| Code  | S00287                                     |
| Item  | SYNERGIC PRO MIG 485                       |
| Input Voltage                                     | 3x230/400V 50-60Hz                         |
| Absorbed power                                    | 40% 15,8 kVA - 60% 10,6 kVA - 100% 7,7 kVA |
| MIN-MAX Welding current                           | 35 – 400 A                                 |
| Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1 | 40% 350A - 60% 290A - 100% 220A            |
| Regulation steps                                  | N° 2x8                                     |
| Wire size (solid)                                 | Ø 0,6 - 0,8 – 1 - 1,2 mm SOLID             |
| Max. wire spool size                              | Ø 300 mm / 15 kg.                          |
| Protection class                                  | IP21                                       |
| Construction standards                            | EN 60974 – 1 / EN 60974 - 10               |
| Dimensions  | 558x980x1330h mm                           |
| Weight  | 134 kg                                     |

**Accessorios:**

309269 (optional) Helmet with auto-dimming LCD filter (9-13 DIN) MAXIVISION COLOR to protect face and eyes during welding.

---



550030 (optional) WF 20 - 2-roll wire feeder

---



550031 (optional) WF 40 - 4-roll wire feeder ready for torch cooling unit

---



550025 (optional) SYNERGIC WF 44 - synergic 4-roll wire feeder ready for cooling unit, with digital meter.

---



530337 (optional) 5 m, extension for wire feed unit with copper cable diam. 50 mm<sup>2</sup>.

---



560200 (optional) CU44V - Vertical 4 l cooling unit for torch.

---



540011 (optional) Aluminium welding kit for Ø 0,8 - 1 wire and 3m torch.

---



530338 (optional) 10 m, extension for wire feed unit with copper cable diam. 50 mm<sup>2</sup>.

---



540014 (optional) Aluminium welding kit for Ø 1,2 - 1,6 wire and 3m torch.

---



530361 (optional) 10 m, extension for wire feed unit with copper cable diam. 70 mm<sup>2</sup> ready for cooling unit.

---



357502 (optional) Flowmeter with 2 gas pressure gauges

---



384024 (optional) Adapter for wire reels of 15 kg. D. 300

---



530360 (optional) 5 m, extension for wire feed unit with copper cable diam. 70 mm<sup>2</sup> ready for cooling unit.

---



309073 (optional) Máscara completa con filtro de cristal líquido de oscurecimiento automático con ajuste de tono variable (9-13DIN) para la protección de la cara y los ojos durante las aplicaciones de corte y soldadura.

---



535015 (optional) antorche M 36, 3 m

---



535016 (optional) Antorche M 36, 4 m

---



535020 (optional) Antorcha MB 501D, 4 m, predisposta para la refrigeración con líquido

---



535019 (optional) Antorcha MB 501D, 3 m, predisposta para la refrigeración con líquido

---