Elettro C.F. s.r.l.
via Miglioli, 24 40024 - Castel San Pietro Terme (Bologna) Italy
Telefono +39 051941453 - +39 0516942026 - FAX +39 051944602
C.F. e Registro Imprese BO n. 00706680378 - P.I. 00521381202 - Capitale Sociale 72.320,00 i.v.

Les détails du produit:

Code: C00410 **Modèle:**BOOSTER 3600



PORTABLE PROFESSIONAL START BOOSTER AND RECHARGEABLE POWER SOURCE

It is ideal for any application where a portable powerful quick-start or/and a long lasting power source is needed.
It's indicated for a high number of starts even if very intensive and doesn't need to be recharged frequently.
It can be powered by connection to the mains electrical supply.
It can be stored in any position without the risk of acid leakage.
It's recommended for coaches, road haulage fleets, vehicles with particular difficulties in charge, graders and bulldozers.

It can be used as:
•An emergency starter.
•An additional power source for vehicles (memory saver).
•A multipurpose additional power source (for electrical 24V devices).

It comes with:
•20A automatic thermal protection,
•protection circuit against peak tensions to protect the vehicle electronic system,
•sound warning in case of polarity reversal,
•polarity test,
•charge test button,
•external safety fuse,
•digital voltmeter,
•insulated clamps with LED,
•batteries with HD technology,
•trolley.
It delivers 3600 peak amps and a minimum of 1300 constant amps.
INCLUDING, AS STANDARD: power supply LESA 7A, clamps with 6-wire copper cable and LED.

Elettro C.F. s.r.l.
via Miglioli, 24 40024 - Castel San Pietro Terme (Bologna) Italy
Telefono +39 051941453 - +39 0516942026 - FAX +39 051944602
C.F. e Registro Imprese BO n. 00706680378 - P.I. 00521381202 - Capitale Sociale 72.320,00 i.v.

Fiche technique:

Code	C00410
Item	BOOSTER 3600
Supply voltage (single phase)	230 V
Voltage	24 V
Peak current output	3600 A
Constant current output	1300 A
Charge voltage	max 25,2 V
Recharge voltage	24V 2Ah
Automatic power supply	LESA 7A
Charging cable 12V	NO
Insulated clamps	YES with LED
Sealed and maintenance free battery	2 x 31Ah
Overload protection	YES
Number of batteries	2
Weight	30 kg
Dimensions	300x350x510h mm
Cable length	1600 mm
Cables section	50 mm2

Accessoires:



LESA7A LESA 7A