

Les détails du produit:

Code: S00140

Modèle: MMA 1425 INVERTER

This INVERTER portable generator has been designed and produced for maintenance operations and assembling of external plants. It allows welding with rutile ad basic coated electrodes.

It features:

- Arc force.
- Hot start.
- Anti-stick.
- Contact TIG starting.
- Possibility to be connected to household mains or to motor-driven generators with an electronic regulator of the tension (not greater than 260V RMS) and a power equal to or greater than 5,5 kVA.
- Equipped with strong shoulder strap.
- Small dimensions and light weight.
- On request, is available complete with suitcase and accessories.



Fiche technique:

Code	S00140
Item	MMA 1425 INVERTER
Input Voltage	1x230V 50-60Hz
Installation power	2,5 kW
MIN-MAX Welding current	10 ÷ 140 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	20% 130A - 60% 90A - 100% 70A
Electrodes	∅ 1,6 ÷ 3,2 mm
Construction standards	EN60974-1 EN60974-10
Dimensions	135x290x230h mm
Weight	4,5 kg

Accessoires:



590007 (optional) Case for power source and accessories



540112 (optional) Set of accessories for electrode welding (rubber cables of \varnothing 16 mm², length 3+2 m)



357502 (optional) Flowmeter with 2 gas pressure gauges



535710 (optional) 4 m, SR 17 V torch, texas D. 25



530149 (optional) Earth cable



S01703A.1 (optional) Accessories kit for electrode welding with 3+2 m cables of 16 mm², Texas 25