

Produktdetail:

Code: C00622

Vorlage: LEM1238

ELECTRONIC BATTERY CHARGER

Electronic and automatic battery charger with charge maintenance function,

- suitable for charging lead batteries: WET, MF, GEL, AGM, Ca/Ca,
- checks and performs a charging automatic cycle that is managed by a microprocessor, in 9 distinct stages, according to the charge conditions of the battery to be charged,
- minimises battery charging time, thanks to its charging characteristic: constant current – constant voltage,
- through its pulse charge maintenance function, it monitors batteries and keeps them charged during idle periods, allowing long time connection to batteries,
- features a special function of rescuing a deeply discharged battery,
- designed to protect vehicle electronics,
- non-sparking,
- protected against polarity reversal,
- battery failure and wrong voltage protection.



INCLUDING, AS STANDARD: connecting clamps, connector for lighter socket.

Datenblatt:

Code	C00622
Item	LEM1238
Input Voltage	1x220-240V 50/60 Hz
Charge voltage	12 V
Conventional charge current arithm EN 60335-2-29	12V 0,8A - 12V 3,8A
Rechargeable battery range	1,2-14Ah (12V-0,8A) - 14-75Ah (12V-3,8A)
Charging stages	n. 9
Battery types	WET, MF, GEL, AGM, Ca-Ca
Protection class	IP 65
Dimensions	175x65x43,5 mm
Weight	0,460 kg

Zubehör:



321613 Insulated, non-sparking, clamps for battery connection.



321614 Connector for lighter socket
