

Produktdetail:

Code: S00259

Vorlage:MIG 3300

Three-phase compact MIG MAG welding machine, on wheels, supplied with M 25 welding torch and earth cable.

- It's available also a model with a 4 roller wire feeder.
- It's suitable to weld steel, stainless steel and aluminium.
- Possibility to adjust the welding parameters through 14 adjustment steps.
- Aluminium wire feeder that enables the adjustment of the pressure applied to the wire for having constant feeding and for decreasing wear of the feeding device.
- Possibility to adjust the spot welding time.
- Highly stable thanks to large-diameter rear wheels.



Datenblatt:

Code	S00259
Item	MIG 3300
Input Voltage	3x230/400V 50-60Hz
Absorbed power	30% 11,5 kVA - 60% 8,3 kVA - 100% 6,5 kVA
MIN-MAX Welding current	25 – 300 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	30% 250A - 60% 180A - 100% 140A
Regulation steps	N° 2 x 7
Wire size (solid)	Ø 0,6 -0,8 - 1,0 - (1,2) mm SOLID
Max. wire spool size	Ø 300 mm / 15 kg.
Protection class	IP21
Construction standards	EN 60974 – 1 / EN50199
Dimensions	506x897x872h mm
Weight	70 kg

Zubehör:



309269

(optional)

Helmet with auto-dimming LCD filter (9-13 DIN) MAXIVISION COLOR to protect face and eyes during welding.



540011

(optional)

Aluminiumset für Drähte \varnothing 0,8 - 1 und für 3m Brenner.



540014

(optional)

Aluminiumset für Drähte \varnothing 1,2 - 1,6 und für 3m Brenner.



357502

(optional)

Druckminderer mit 2 Manometern



384024

(optional)

Adapter for wire reels of 15 kg. D. 300



309073

(optional)

Helm mit LCD-Filter (9-13 DIN).



535013

M 25 Brenner, 3 m



535014

(optional)

M 25 Brenner, 4 m