

Produktdetail:

Code: S00256

Vorlage: MIG 280

Three-phase compact MIG MAG welding machine, on wheels, supplied with M 15 welding torch and earth cable. It's available also with a 4 roller wire feeder and a 4 m long torch.

- It is suitable to weld iron, steel, stainless steel and aluminium.
- Aluminium wire feeder: it enables to adjust the pressure applied to the wire for having constant feeding and for decreasing wear of the feeding device.
- Possibility to adjust the spot welding time.
- Highly stable thanks to large-diameter rear wheels.



Datenblatt:

Code	S00256
Item	MIG 280
Input Voltage	3x230/400V 50-60Hz
Absorbed power	50% 8,5 kVA - 60% 7,2 kVA - 100% 4,3 kVA
MIN-MAX Welding current	20 – 250 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	50% 200A - 60% 180A - 100% 140A
Regulation steps	N° 1 x 7
Wire size (solid)	Ø 0,6 -0,8 - 1,0 mm SOLID
Max. wire spool size	Ø 300 mm / 15 kg.
Protection class	IP21
Construction standards	EN 60974 – 1 / EN60974-10
Dimensions	506x897x872h mm
Weight	69 kg

Zubehör:



540011 (optional) Aluminiumset für Drähte \varnothing 0,8 - 1 und für 3m Brenner.



309263 (optional) Welding helmet with auto-dimming LDC filter BEST VISION,



535011 3 m, M 15 Brenner



535012 M 15 Brenner, 4 m
