

Produktdetail:

Code: S00275

Vorlage:PRO MIG 558

Tri-phase MIG-MAG welding equipment with separate wire feeder.
Supplied complete with earth cable and reel of wire.

- Predisposition to use water-cooled torches (together with cooling unit).
- 4-roll wire feeder.
- Suitable for steel, stainless steel and aluminium welding.
- Thermostat warning light.
- “EURO” torch connection.
- High number of adjustments to facilitate achievement of the best parametres.
- Copper windings.
- Three impedance adjustment positions.
- Digital ammeter and voltmeter

Different voltages available on request



Datenblatt:

Code	S00275
Item	PRO MIG 558
Input Voltage	3x230/400V 50-60Hz
Absorbed power	60% 26kVA - 100% 18kVA
MIN-MAX Welding current	35 – 500 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	60% 500A - 100% 390A
Regulation steps	N° 32
Wire size (solid)	∅ mm 0,8 – 1 – 1,2 – 1,6
Max. wire spool size	∅ 300 mm / 15 kg.
Protection class	IP21
Construction standards	EN 60974 – 1 / EN50199
Dimensions	mm 460x1110x1285h
Weight	195 kg

Zubehör:

550011 (optional) Four-roller wire feed unit equipped with 1,3 m extension



560000 (optional) Vertical 5 l cooling unit for torch



535019 (optional) 3 m, MB 501D Brenner, vorbereitet für Wasserkühlung



535020 (optional) 4 m, MB 501D Brenner, vorbereitet für Wasserkühlung



535017 (optional) 3 m, MB 40 torch



535018 (optional) 4 m, MB 40 torch

530320 (optional) 4 m extension for 4-roller wire feed unit, ready for cooling unit

530321 (optional) 9 m extension for 4-roller wire feed unit, ready for cooling unit
