

Produktdetail:

Code: P00482

Vorlage: PLASMA 51 PFC INVERTER

The single-phase power source with inverter technology for metal plasma cutting, PLASMA 51 PFC INVERTER, is characterised by compact design, low weight, easy handling, user-friendliness, cutting high-efficiency on small and medium thicknesses.

The price - cutting quality ratio means this power source is suitable for a variety of applications, from maintenance to shipyards, to the small blacksmith shop.

The recommended cutting thickness on steel is from 13 mm to 20 mm. The separation thickness is 25 mm.

The lack of High-Frequency start makes it possible to work next to computers, medical equipment, instruments and any other electronic devices sensitive to high frequency emissions.

It can be connected to motor-driven generators of adequate power.



MAIN FEATURES

- Pilot Arc to cut painted or coated metals.
- Suitable for plasma gouging.
- Self Restart Pilot function for nets and grids cutting.
- Ultra Cut Capacity technology to improve the cutting capacities on high thicknesses.
- Innovative Thin Cut technology that allows to obtain cuts of superior quality and reduced kerf (amount of removed material).
- Hyper Speed Cut technology enhancing the cutting speed.
- Multi Piercing technology: possibility of piercing on high thickness in a shorter time and with less wear of consumables.
- Extra Life technology and Low Pilot Arc technology that increases performances and duration of consumables.
- Long Tip technology allowing to cut close to very narrow angles and small spaces.
- Microprocessor-controlled cutting parameters and functions.
- Safety systems on the torch.
- Its standard equipment includes a 6 meter-long hand torch and a grounding cable.

Datenblatt:

Code	P00482
Item	PLASMA 51 PFC INVERTER
Input Voltage	1x230V 50-60HZ
Absorbed power	40% 8,5 kVA - 60% 7,1 kVA - 100% 6 kVA
Cutting current	10 ÷ 50 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	40% 50A - 60% 42A - 100% 35A
Air pressure	5 bar
Air flow	170 l/min
Cut thickness on steel	13 - 20 mm
Max separation cut	25 mm
Piercing	10 mm
Protection class	IP 23
Construction standards	EN60974 – 1 / EN60974 – 7 / EN60974 – 10
Dimensions	220x440x460h mm
Weight	17 kg

Zubehör:

 535442 6 m, hand torch ECF-71


 535441 (optional) 12m, hand torch ECF-71


 535440 (optional) 6m, machine torch ECF-71




535439 (optional) 12m, machine torch ECF-71



540130.B (optional) MINI KIT für Handbrenner ECF-71 - ECF-121 (45A)

2 x  356555

1 x  356556

2 x  356557

540087.B

540087.B (optional) Consumables kit for first use.



309464 (optional) Wheeled compasses for ST-70 / ECF-71 ST-120



356437 (optional) Wheeled torch holder for ST-70 / ECF-71 ST-120



356436 (optional) Fasenwerkzeugsatz zum Plasmaschneiden



580002 (optional) Fahrwagen für Transport



309489 (optional) Non-stick spray



357227 (optional) Compressed air filter with filtering cartridge to protect torches against impurities present in compressed air (oil and/or water).



370001 (optional) Cartridges for air filter, package of 8 pieces.



309073 (optional) Helm mit LCD-Filter (9-13 DIN).
