

Produktdetail:

Code: S00300

Vorlage:SYNERGIC PRO MIG 520

Three-phase power source for MIG MAG continuous wire welding of steel, stainless steel and aluminium. It is equipped with a synergic, 4-roller, wire feed unit item SYNERGIC WF45 and is ready for the use with water cooled torches. Possibility to connect extensions for the connection of power sources to wire feed units of 5 or 10 metres.

Equipped with:

- Timer circuit to automatically switch the power source to stand-by mode when not welding, to prevent unnecessary power consumption.
- Multiple impedance outlet for improved welding characteristic adjustment.
- Microprocessor, for automatic welding current and wire speed adjustment via a wide range of pre-stored programs.
- Synergic wire feed unit with digital instrument that allows to handle welding parameters such as tack welding, soft start, burn-back, post gas and 2 stage – 4 stage (manual – automatic) welding modes.
- Possibility to use reels of wire with a weight of 15 kg and a diameter of 300 mm.
- Highly stable thanks to large-diameter rear wheels
- Signal of intervention of the thermostat.



Datenblatt:

Code	S00300
Item	SYNERGIC PRO MIG 520
Input Voltage	3x230/400V 50-60Hz
Absorbed power	40% 19,5KVA
MIN-MAX Welding current	40 – 450 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	40% 400A - 60% 330A - 100% 250A
Regulation steps	N° 4x8
Wire size (solid)	Ø 0,8 – 1 - 1,2 - (1,6) mm SOLID
Max. wire spool size	Ø 300 mm / 15 kg.
Protection class	IP21
Construction standards	EN 60974 – 1 / EN 60974 - 10
Dimensions	558x980x1330h mm
Weight	153 kg

Zubehör:


535019 (optional) 3 m, MB 501D Brenner, vorbereitet für Wasserkühlung



535020 (optional) 4 m, MB 501D Brenner, vorbereitet für Wasserkühlung



535015 (optional) 3 m, M 36 Brenner



535016 (optional) 4 m, M 36 Brenner



550026 SYNERGIC WF 45 - synergic 4-roll wire feeder ready for cooling unit, with digital meter.



309269 (optional) Helmet with auto-dimming LCD filter (9-13 DIN) MAXIVISION COLOR to protect face and eyes during welding.



530361 (optional) 10 m, Verlängerungskabel aus Kupfer mit D. 70 mm² vorbereitet für Wasserkühlung.



357502 (optional) Druckminderer mit 2 Manometern



530360 (optional) 5 m, Verlängerungskabel aus Kupfer mit D. 70 mm² vorbereitet für Wasserkühlung.



309073 (optional) Helm mit LCD-Filter (9-13 DIN).



530337 (optional) 5 m, Verlängerungskabel aus Kupfer mit D. 50 mm²



560200 (optional) CU44V - Vertical 4 l cooling unit for torch.



540011 (optional) Aluminiumset für Drähte Ø 0,8 - 1 und für 3m Brenner.



530338 (optional) 10 m, Verlängerungskabel aus Kupfer mit D. 50 mm².



540014 (optional) Aluminiumset für Drähte \varnothing 1,2 - 1,6 und für 3m Brenner.
