

Les détails du produit:

Code: S00172

Modèle: ECF-2000

Inverter power source for MMA and TIG welding. Especially indicated for maintenance operations and installation of outside plants. It allows welding with rutile ad basic coated electrodes.

It features:

- Arc Force,
- Hot Start,
- Anti-Stick,
- Lift-arc TIG starting,
- Display,
- MMA-TIG selector.

Supplied complete with carrying case and accessories.



Fiche technique:

| | |
|---|---------------------------------|
| Code | S00172 |
| Item | ECF-2000 |
| Input Voltage | 1x230V 50-60Hz |
| Installation power | 4,5 kW |
| MIN-MAX Welding current | 10 ÷ 200 A |
| Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1 | 25% 200A - 60% 150A - 100% 100A |
| Electrodes | Ø 1,6 ÷ 5 mm |
| Protection class | IP23 |
| Construction standards | EN60974-1 EN60974-10 |
| Dimensions | 120X300X220h mm |
| Weight | 6 kg |

Accessoires:



ACC172 Accessories



VLG172 Case for power source and accessories



357502 (optional) Flowmeter with 2 gas pressure gauges



530138 (optional) Câble de terre pour le soudage



535717 (optional) 4m, ABITIG 26V TIG torch
