

Les détails du produit:

Code: S00173

Modèle: ECF-1400

Onduleur monophasé pour souder à l'arc à l'électrode enrobée (MMA) et en TIG. Grâce à ses dimensions et son poids très réduits, il est particulièrement indiqué pour les travaux d'entretien.

Il consent le soudage d'électrodes enrobées rutiles et basiques.

Pourvu de :

- Arc Force,
- Hot Start,
- Anti-Stick,
- Amorçage TIG au toucher (lift-arc).
- Possibilité d'être alimenté par un moto-générateur avec une puissance adéquate,
- Robuste sangle pour le transport en bandoulière.

Livré complet avec valise et accessoires.



Fiche technique:

| | |
|---|-------------------------------|
| Code | S00173 |
| Item | ECF-1400 |
| Input Voltage | 1x230V 50-60Hz |
| Installation power | 2,5 kW |
| MIN-MAX Welding current | 10 ÷ 140 A |
| Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1 | 25% 140A - 60% 95A - 100% 80A |
| Electrodes | Ø 1,6 ÷ 3,2 mm |
| Protection class | IP21 |
| Construction standards | EN60974-1 |
| Dimensions | 100x255x160h mm |
| Weight | 3,5 kg |

Accessoires:



VLG171 Case for power source and accessories



ACC171 Accessories



357502 *(optional)* Flowmeter with 2 gas pressure gauges



535710 *(optional)* 4 m, SR 17 V torch, texas D. 25



530149 *(optional)* Earth cable
