

Les détails du produit:

Code: S00270

Modèle: MIG 2400/A

Générateur pour souder à fil continu MIG-MAG, sur roues, avec porte-bouteille, livré avec torche TE140 et câble de masse.

- Il permet de souder l'acier, l'acier inox et l'aluminium.
- Possibilité de gérer les paramètres de soudure grâce à 7 positions de réglage.
- Possibilité d'utiliser des bobines de fil de kg 15 et 300 mm de diamètre.
- Signal d'intervention du thermostat.



Fiche technique:

Code	S00270
Item	MIG 2400/A
Input Voltage	3x230/400V 50-60Hz
Absorbed power	35% 6,0 kVA - 60% 4,6 kVA - 100% 3,5 kVA
MIN-MAX Welding current	15 – 220 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	35% 170A - 60% 130A - 100% 100A
Regulation steps	N° 1 x 7
Wire size (solid)	∅ mm 0,6 -0,8 - (1,0) SOLID
Max. wire spool size	∅ 300 mm / 15 kg.
Protection class	IP21
Construction standards	EN 60974 – 1 / EN 60974 - 10
Dimensions	506x887x648h mm
Weight	53 kg

Accessoires:



535005 2,2 m, TE 140 torch with direct connection



530180 Earth cable



384024 *(optional)* Adapter for wire reels of 15 kg. D. 300



309073 *(optional)* Helmet with variable shade auto-darkening LCD filter (9-13 DIN) to protect face and eyes during cutting and welding appliances.



309269 *(optional)* Helmet with auto-dimming LCD filter (9-13 DIN) MAXIVISION COLOR to protect face and eyes during welding.



357502 *(optional)* Flowmeter with 2 gas pressure gauges
