

Produktdetail:

Code: P00446**Vorlage:** THUNDER CUT 105

The three-phase power source with inverter technology for metal plasma cutting, THUNDER CUT 105, has been designed for the professional manual cutting sector and offers maximum performance and optimised processing times.

It is characterised by compact design, low weight, easy handling, user-friendliness, cutting high-efficiency on small and medium thicknesses.

Cutting thicknesses are high in relation to delivered current, it is suitable for medium-heavy applications.

The recommended steel thickness is from 36 mm to 42 mm. The separation thickness is 55 mm. The max. piercing is 20 mm.

The lack of High-Frequency start makes it possible to work next to computers, medical equipment, instruments and any other electronic devices sensitive to high frequency emissions.



MAIN FEATURES


- The new ESA Fast connector that allows the torch to be connected and disconnected quickly, no tools are needed.
- A single knob for fine-tuning the cutting current quickly.
- The possibility of interrupting the post-gas function to quickly replace exhausted consumables.
- The practical quick coupling of the pressure regulator.
- Pilot Arc to cut painted or coated metals.
- Suitable for plasma gouging.
- Self Restart Pilot function for nets and grids cutting.
- Ultra Cut Capacity technology to improve the cutting capacities on high thicknesses.
- Innovative Thin Cut technology that allows to obtain cuts of superior quality and reduced kerf (amount of removed material).
- Hyper Speed Cut technology enhancing the cutting speed.
- Extra Life technology and Low Pilot Arc technology that increases performances and duration of consumables.
- Long Tip technology allowing to cut close to very narrow angles and small spaces.
- Microprocessor-controlled cutting parameters and functions.
- Safety systems on the torch.
- Its standard equipment includes a 6 meter-long hand torch ECF-121 with its starting kit of consumables and a grounding cable.

Datenblatt:

Code	P00446
Item	THUNDER CUT 105
Input Voltage	3x400V 50-60HZ
Absorbed power	45% 16,8 kVA - 60% 15,2 kVA - 100% 13,6 kVA
Cutting current	15 ÷ 105 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	45% 105 A - 60% 95 A - 100% 85 A
Air pressure	5,5 bar
Air flow	250 l/min
Cut thickness on steel	36 - 42 mm
Max separation cut	55 mm
Piercing	20 mm
Protection class	IP 23
Construction standards	EN60974 – 1 / EN60974 – 7 / EN60974 – 10
Dimensions	220x540x460h mm
Weight	23 kg

Zubehör:


535408 Handbrenner ECF-121, 6m



540118.B Starting kit für Brenner ECF-121 (105A)



535407 (optional) Handbrenner ECF-121, 12m

540165.B *(optional)* MINI KIT für Handbrenner ECF-121 (105A)



309464 *(optional)* Wheeled compasses for ST-70 / ECF-71 ST-120



356437 *(optional)* Wheeled torch holder for ST-70 / ECF-71 ST-120



356436 *(optional)* Fasenwerkzeugsatz zum Plasmaschneiden



580006 *(optional)* Fahrwagen für Transport



309489 *(optional)* Non-stick spray



309073 *(optional)* Helm mit LCD-Filter (9-13 DIN).



357227 *(optional)* Compressed air filter with filtering cartridge to protect torches against impurities present in compressed air (oil and/or water).



370001 *(optional)* Cartridges for air filter, package of 8 pieces.
