

Product Detail:

Code: P00492

Model: PLASMA 95

Tri-phase power source for plasma cutting suitable for any cutting requirement on any kind of metal.

It features excellent cutting speed and performance. It can cut up to 25 mm on steel and separate up to 30 mm and it is suitable for light-medium metal fabrication as well as servicing in general.

The cutting current is not affected by mains voltage variations, change in the distance between the torch and the piece you are cutting or the speed at which you move forward.

Configuration at delivery including 6 m P150 torch and earth cable.

MAIN FEATURES

- Pilot arc
- High-frequency starting
- Electric protection system on the torch
- Compressed air flow control
- Thermal protection by thermostat
- Copper windings

Different voltages available on request



Technical Data:

Code	P00492
Item	PLASMA 95
Input Voltage	3x400V 50Hz
Absorbed power	40% 18,4kVA - 90% 12,5kVA
Cutting current	60 - 90 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	40% 90A - 90% 60A
Air pressure	5 bar
Air flow	180 l/min
Cut thickness on steel	25 mm
Max separation cut	30 mm
Protection class	IP21
Construction standards	EN 60974 – 1 / EN50199
Dimensions	460x720x980h mm
Weight	115 kg

Accessories:



535487 6 m, P 150 hand torch, central adaptor



535494 *(optional)* 12 m, P 150 hand torch, central adaptor



535486 *(optional)* 6 m, P 150 machine torch, central adaptor



535496 *(optional)* 12 m, P 150 machine torch, central adaptor



356502 *(optional)* Wheeled torch holder for P150



309488 *(optional)* Wheeled compasses for P150
