

## Detalle del producto:

**Código:** P00497

**Modelo:** PLASMA 106 INVERTER

MULTI-VOLTAGE THREE-PHASE DC POWER SOURCE WITH INVERTER TECHNOLOGY FOR PLASMA CUTTING

Thanks to its inverter technology combines compact dimensions and low weight with excellent cutting performances, up to 30 mm thick on steel (separation up to 35 mm).

Configuration at delivery including 6 m P150 torch and earth cable.

- Automatic setting of appropriate voltage within the following ranges: 3x208/220/230V e 400/440V,
- Automatic detection of phase presence both upon start-up and during operation,
- Pilot arc,
- High Frequency/Voltage start,
- “Post-gas” function,
- Safety systems on the torch,
- Control and gauge for the presence of compressed air flow and thermostatic protection.
- Microprocessor-controlled cutting parameters and functions.
- Self Restart Pilot function for nets and grids cutting.
- Cutting current is not affected by voltage fluctuations, by change of distance between torch and piece as well as by the torch travelling speed.
- Possibility to be connected to motor-driven generators.



**Ficha de datos:**

Code	P00497	
Item	PLASMA 106 INVERTER	
Input Voltage	3x208-220-230V 50-60HZ	3x400-440V 50-60HZ
Absorbed power	35% 13,6kVA	50% 16,5kVA
Cutting current	20÷80 A	20÷100 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	35% 80A - 60% 65A - 100% 58A	50% 100A - 60% 95A - 100% 85A
Air pressure	5 bar	
Air flow	220 l/min	
Cut thickness on steel	25 - 30 mm	
Max separation cut	35 mm	
Protection class	IP 23 C	
Construction standards	EN60974 – 1 / EN60974 – 7 / EN60974 – 10	
Dimensions	330x600x540h mm	
Weight	38 kg	

**Accesorios:**

 2 x  356476

 1 x  356477

 2 x  356478

**540083.B**
**540083.B (optional) Consumables kit for first use.**

**540051 (optional) Computer-pantograph kit**

**580003 (optional) Transport cart**



309073 (optional)

Máscara completa con filtro de cristal líquido de oscurecimiento automático con ajuste de tono variable (9-13DIN) para la protección de la cara y los ojos durante las aplicaciones de corte y soldadura.



309071 (optional)

Gafas de lente única con patillas ajustables y protección lateral incorporada. Lente de policarbonato para protección contra impactos mecánicos y procesos de corte.



309072 (optional)

Guantes de piel bovina y tela de algodón, reforzados en la palma, índice y pulgar.



309092 (optional) Cincel para remover la escoria



535487 6 m, P 150 hand torch, central adaptor



535494 (optional) 12 m, P 150 hand torch, central adaptor



535486 (optional) 6 m, P 150 machine torch, central adaptor



535496 (optional) 12 m, P 150 machine torch, central adaptor



356502 (optional) Wheeled torch holder for P150



309488 (optional) Wheeled compasses for P150