

Les détails du produit:

Code: P00497

Modèle: PLASMA 106 INVERTER

MULTI-VOLTAGE THREE-PHASE DC POWER SOURCE WITH INVERTER TECHNOLOGY FOR PLASMA CUTTING

Thanks to its inverter technology combines compact dimensions and low weight with excellent cutting performances, up to 30 mm thick on steel (separation up to 35 mm).

Configuration at delivery including 6 m P150 torch and earth cable.

- Automatic setting of appropriate voltage within the following ranges: 3x208/220/230V e 400/440V,
- Automatic detection of phase presence both upon start-up and during operation,
- Pilot arc,
- High Frequency/Voltage start,
- “Post-gas” function,
- Safety systems on the torch,
- Control and gauge for the presence of compressed air flow and thermostatic protection.
- Microprocessor-controlled cutting parameters and functions.
- Self Restart Pilot function for nets and grids cutting.
- Cutting current is not affected by voltage fluctuations, by change of distance between torch and piece as well as by the torch travelling speed.
- Possibility to be connected to motor-driven generators.



Fiche technique:

Code	P00497		
Item	PLASMA 106 INVERTER		
Input Voltage	3x208-220-230V 50-60HZ	3x400-440V 50-60HZ	
Absorbed power	35% 13,6kVA	50% 16,5kVA	
Cutting current	20÷80 A	20÷100 A	
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	35% 80A - 60% 65A - 100% 58A	50% 100A - 60% 95A - 100% 85A	
Air pressure	5 bar		
Air flow	220 l/min		
Cut thickness on steel	25 - 30 mm		
Max separation cut	35 mm		
Protection class	IP 23 C		
Construction standards	EN60974 – 1 / EN60974 – 7 / EN60974 – 10		
Dimensions	330x600x540h mm		
Weight	38 kg		

Accessoires:

 2 x  356476

 1 x  356477

 2 x  356478

540083.B
540083.B (optional) Consumables kit for first use.

535487 6 m, P 150 hand torch, central adaptor

535494 (optional) 12 m, P 150 hand torch, central adaptor



535486 (optional) 6 m, P 150 machine torch, central adaptor



535496 (optional) 12 m, P 150 machine torch, central adaptor



356502 (optional) Wheeled torch holder for P150



309488 (optional) Wheeled compasses for P150



309073 (optional) Helmet with variable shade auto-darkening LCD filter (9-13 DIN) to protect face and eyes during cutting and welding appliances.



309071 (optional) Single lens spectacles with adjustable temples and built in side-protections. Polycarbonate lens for protection against mechanical impacts and cutting processes.



309072 (optional) Gloves in cow crust leather and cotton, with reinforced palm, index and thumb.



309092 (optional) Chisel to remove dross



580003 (optional) Transport cart



540051 (optional) Computer-pantograph kit
