

## Product Detail:

**Code:** S00274

**Model:**PRO MIG 458

MIG-MAG continuous wire welding tri-phase system with separate wire feed unit. It is ready for water-cooling of the torch. Equipped with earth cable and reel of wire.

- Separate four-roller wire feed unit.
- Suitable for welding of steel, stainless steel and aluminium.
- Signal of intervention of the thermostat.
- “EURO” type connection for the torch.
- High number of adjustments to facilitate achievement of the best parameters.
- Copper windings.
- Three impedance adjustment positions.
- Digital ammeter and voltmeter

Different voltages available on request



**Technical Data:**

Code	S00274
Item	PRO MIG 458
Input Voltage	3x230/400V 50-60Hz
Absorbed power	60% 19,8KVA - 100% 11,8kVA
MIN-MAX Welding current	35 – 450 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	60% 420A - 100% 330A
Regulation steps	N° 32
Wire size (solid)	∅ mm 0,8 – 1 – 1,2 – 1,6
Max. wire spool size	∅ 300 mm / 15 kg.
Protection class	IP21
Construction standards	EN 60974 – 1 / EN50199
Dimensions	mm 460x1110x1285h
Weight	185 kg

## Accessories:

550011 (optional) Four-roller wire feed unit equipped with 1,3 m extension

---



560000 (optional) Vertical 5 l cooling unit for torch

---



535019 (optional) 3 m, MB 501D torch, ready for cooling unit

---



535020 (optional) 4 m, MB 501D torch, ready for cooling unit

---



535017 (optional) 3 m, MB 40 torch

---



535018 (optional) 4 m, MB 40 torch

---

530320 (optional) 4 m extension for 4-roller wire feed unit, ready for cooling unit

---

530321 (optional) 9 m extension for 4-roller wire feed unit, ready for cooling unit

---