

Produktdetail:

Code: S00239

Vorlage:MIG 308

MIG-MAG continuous wire welding tri-phase system with separate wire feed unit. Supplied with MB 25 welding torch, earth cable, reel of wire.

- Separate two-roller wire feed unit.
- Suitable for welding of steel, stainless steel and aluminium.
- Signal of intervention of the thermostat.
- “EURO” type connection for the torch.
- High number of adjustments to facilitate achievement of the best parametres.

Different voltages available on request



Datenblatt:

Code	S00239
Item	MIG 308
Input Voltage	3x230/400V 50-60Hz
Absorbed power	40% 11,2kVA - 60% 7,2kVA - 100% 5,6 KVA
MIN-MAX Welding current	25 – 250 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	40% 250A - 60% 200A - 100% 160A
Regulation steps	N° 14
Wire size (solid)	Ø mm 0,6 -0,8 – 1 – 1,2
Max. wire spool size	Ø 300 mm / 15 kg
Protection class	IP21
Construction standards	EN 60974 – 1 / EN50199
Dimensions	mm 410x970x1170h
Weight	111 kg

Zubehör:



535013 M 25 Brenner, 3 m



535014 *(optional)* M 25 Brenner, 4 m

550010 Two-roller wire feed unit equipped with 1,3 m extension

530316 *(optional)* 4 m extension for 2-roller wire feed unit

530317 *(optional)* 9 m extension for 2-roller wire feed unit
