

Product Detail:

Code: S00240

Model: MIG 348

MIG-MAG continuous wire welding tri-phase system with separate wire feed unit. Supplied with MB 36 welding torch, earth cable and reel of wire.

- Separate two-roller wire feed unit.
- Suitable for welding of steel, stainless steel and aluminium.
- Signal of intervention of the thermostat.
- “EURO” type connection for the torch.
- High number of adjustments to facilitate achievement of the best parametres.
- Copper windings.



Different voltages available on request

Technical Data:

Code	S00240
Item	MIG 348
Input Voltage	3x230/400V 50-60Hz
Absorbed power	40% 14,5 KVA - 60% 10,8 KVA - 100% 7,2 KVA
MIN-MAX Welding current	30 – 300 A
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	40% 300A - 60% 250A - 100% 190A
Regulation steps	N° 14
Wire size (solid)	Ø mm 0,6 -0,8 – 1 – 1,2
Max. wire spool size	Ø 300 mm / 15 kg
Protection class	IP21
Construction standards	EN 60974 – 1 / EN50199
Dimensions	mm 410x970x1170h
Weight	121 kg

Accessories:



535015 3 m, M 36 torch



535016 *(optional)* 4 m, M 36 torch

550010 Two-roller wire feed unit equipped with 1,3 m extension
