

Les détails du produit:

Code: S00240

Modèle: MIG 348

MIG-MAG continuous wire welding tri-phase system with separate wire feed unit. Supplied with MB 36 welding torch, earth cable and reel of wire.

- Separate two-roller wire feed unit.
- Suitable for welding of steel, stainless steel and aluminium.
- Signal of intervention of the thermostat.
- “EURO” type connection for the torch.
- High number of adjustments to facilitate achievement of the best parametres.
- Copper windings.



Different voltages available on request

Fiche technique:

| | |
|---|--|
| Code | S00240 |
| Item | MIG 348 |
| Input Voltage | 3x230/400V 50-60Hz |
| Absorbed power | 40% 14,5 KVA - 60% 10,8 KVA - 100% 7,2 KVA |
| MIN-MAX Welding current | 30 – 300 A |
| Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1 | 40% 300A - 60% 250A - 100% 190A |
| Regulation steps | N° 14 |
| Wire size (solid) | Ø mm 0,6 -0,8 – 1 – 1,2 |
| Max. wire spool size | Ø 300 mm / 15 kg |
| Protection class | IP21 |
| Construction standards | EN 60974 – 1 / EN50199 |
| Dimensions | mm 410x970x1170h |
| Weight | 121 kg |

Accessoires:



535015 Torche M 36, 3 m



535016 *(optional)* Torche M 36, 4 m

550010 Two-roller wire feed unit equipped with 1,3 m extension
